

FAFCO

Solar Bear

ABOVE GROUND POOL SOLAR HEAT EXCHANGER

DESCRIPTION: The Solar Bear Solar Collector is manufactured in Chico, California. The collector is a specially developed, highly stabilized polyolefin and is of parallel, circular channel design. It is unglazed, uninsulated, and designed for low temperature applications such as swimming pool heating, heat pumps, aquaculture, and hydroponics.

DIMENSIONS: Header Length = 50.875 in. (1.29 m)
Width (Panel body) = 47.5 in. (1.21 m)

Overall Dimensions:	<u>Effective Area</u>
4 ft. X 10 ft. (1.22 X 3.05 m)	39.5 ft ² (3.67 m ²)
4 ft. X 20 ft. (1.22 X 6.10 m)	79.2 ft ² (7.35 m ²)

ROOF MOUNTING SPACE: Width = 50.875 in. (129 cm) + 14 in. (35 cm)
Length = Panel length + 24 in. (61 cm)

RACK SPACE: Width = 50.875 in. (129 cm) + 6 in. (15 cm)
Length = Panel length + 6 in. (15 cm)

FLOW: Maximum recommended flow = 8 gpm per panel
3.47 psi head loss (1,817 l/hr, 0.244 kg/cm²)
Minimum recommended flow = 3 gpm per panel
0.48 psi head loss (681 l/hr, 0.034 kg/cm²)
Recommended flow = 4 gpm per panel
0.87 psi head loss (908 l/hr, 0.061 kg/cm²)

PRESSURE:	NORMAL OPERATING PRESSURE	MAXIMUM INTERMITTENT PRESSURE
80°F (27°C)	0 to 30 psi (0 - 2.11 kg/cm ²)	45 psi (3.16 kg/cm ²)
212°F (100°C)	0 to 5 psi (0 - 0.35 kg/cm ²)	5 psi (0.35 kg/cm ²)
70°F (21°C)	Measured burst pressure of panel body = Over 300 psi (21.1 kg/cm ²)	

TEMPERATURE: Normal operating temperature = 60°F to 90°F (16°C to 32°C)
Maximum continuous operating temperature = 212°F (100°C)
Maximum intermittent temperature (unpressured) = 250°F (121°C)
Melt temperature = 338°F (170°C)

CHEMICAL RESISTANCE: Compatible with common collector fluids

CORROSION: Non-corrosive

FREEZING: The system should be drained before freezing conditions occur.

WEATHERABILITY: Weatherometer, accelerated outdoor exposure, and other extensive laboratory testing demonstrates long-term weatherability of SunSaver™ collectors (see warranty). Additionally, FAFCO's experience of 30 years and over 1,000,000 collectors installed confirms that the proprietary stabilization and high mechanical strength results in negligible warranty over the warranty period.

WEIGHT:

Without Water:

4 ft. X 10 ft. 15.9 lbs (5.93 kg) or 0.40 lbs/ft² (1.95 kg/m²)
4 ft. X 20 ft. 31.8 lbs (14.4 kg) or 0.40 lbs/ft² (1.95 kg/m²)

With Water:

4 ft. X 10 ft. 59.8 lbs (22.3 kg) or 1.50 lbs/ft² (7.32 kg/m²)
4 ft. X 20 ft. 119.6 lbs (54.2 kg) or 1.50 lbs/ft² (7.32 kg/m²)

ABSORPTIVITY: 0.96


EMISSIVITY: 0.90

TIME CONSTANT: 64 seconds


TESTED OUTPUT: 1,014 BTU/ft² (Florida Solar Energy Center)

PERFORMANCE CURVES:


INCIDENT ANGLE CHARACTERISTICS




MEASURED EFFICIENCY
Average flow rate 4.9 gpm (1113 l/hr)
Average wind velocity 2.4 mph (3.9 km/hr)



PRESSURE vs. FLOW



EFFICIENCY vs. FLOW
(for typ. conditions)



All specifications and dimensions set forth above are as estimated by FAFCO Inc., but are not intended to be precise and should not be relied upon as precise without independent verification. These estimated specifications and dimensions are subject to change without notice. Nothing contained herein is intended or should be construed to expand or extend FAFCO Inc.'s warranty, or establish any express or implied warranties of any nature, other than as contained in the Limited Ten Year Warranty Agreement. (FAFCO Inc. disclaims any other warranties and assumes no duty to provide notice if it becomes aware of any deficiencies in these estimates.) The reader accepts full responsibility for any use or application of these estimates and specifically understands and acknowledges the limited reliability of these estimates.